



# CIVILPRO

## GENERATOR & WELDER

# RENTALS & HIRE

0411 961 231 [WWW.CIVILPRO.COM.AU](http://WWW.CIVILPRO.COM.AU)



### PORTABLE POWER

#### Technical

|                               |                                |
|-------------------------------|--------------------------------|
| <b>Model</b>                  | GH 10,000E-FBT                 |
| <b>Type</b>                   | Portable                       |
| <b>Speed</b>                  | 3000 RPM                       |
| <b>Phase/Voltage</b>          | 1/240                          |
| <b>Frequency</b>              | 50 Hz                          |
| <b>Max power kW</b>           | 9.0 kW                         |
| <b>Continuous Output</b>      | 11.0 kVA                       |
| <b>Noise Level (dBA @ 7m)</b> | 74                             |
| <b>Frame</b>                  | Skid Base with Roll Over Frame |

#### Engine

|                         |                     |
|-------------------------|---------------------|
| <b>Manufacturer</b>     | Honda               |
| <b>Engine Model</b>     | GX610               |
| <b>Type</b>             | O.H.V.              |
| <b>Starting</b>         | Electric start      |
| <b>Fuel</b>             | Unleaded Petrol     |
| <b>Run Time</b>         | 4.2hrs @60%         |
| <b>Tank Capacity</b>    | 50 L                |
| <b>HP 3000 rpm cont</b> | 11.9 HP             |
| <b>Cubic Capacity</b>   | 614 Cm <sup>3</sup> |
| <b>Oil Capacity</b>     | 1.8 L               |

#### Alternator

|                            |              |
|----------------------------|--------------|
| <b>Alternator Brand</b>    | Meccalte     |
| <b>Type</b>                | Brushless    |
| <b>Harmonic Distortion</b> | Less than 5% |
| <b>Protection Class</b>    | IP 23        |
| <b>Insulation Class</b>    | Class H      |

#### Outlets

|               |  |
|---------------|--|
| <b>Outlet</b> | 2 x 15amp switched with thermal overload |
|---------------|--|

#### Dimensions & Weight

|               |        |
|---------------|--------|
| <b>Length</b> | 105 Cm |
| <b>Width</b>  | 55 Cm  |
| <b>Height</b> | 70 Cm  |
| <b>Weight</b> | 140 Kg |

#### Options

|                    |  |
|--------------------|--|
| <b>Outlets</b>     | Weather protected IP33 & Weatherproof IP66 |
| <b>Protection</b>  | RCD/ELCB IP30 or IP66                      |
| <b>Wheel kits</b>  | Four wheel                                 |
| <b>Alternators</b> | Oversized, Single or Three Phase           |

POWERED by  
**HONDA**™



The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.