



CIVILPRO

GENERATOR & WELDER

RENTALS & HIRE

0411 961 231

WWW.CIVILPRO.COM.AU



PORTABLE POWER

Technical

Model	GH 2700
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max power kW	2.7kW
Continuous Output	3.3kVA
Noise Level (dBA @ 7m)	72
Frame	Small roll frame

Engine

Manufacturer	Honda
Engine Model	GX200
Type	O.H.V.
Starting	Recoil start
Fuel	Unleaded Petrol
Run Time	2.7hrs @ 100%, 4hrs @ 60% Load
Consumption	1.3 L/h
Tank Capacity	3.6 L
HP 3000 rpm Cont	4.4
Cubic Capacity	196 Cm ³
Oil Capacity	0.6 L

Alternator

Alternator Brand	Meccalte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Outlets

Outlet	10amp + 15amp switched with thermal overload
---------------	--

Dimensions & Weight

Length	67 Cm
Width	44 Cm
Height	48 Cm
Weight	39 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Long Range Tank	15 Litre Capacity

POWERED by
HONDA™

meccalte spa