



CIVILPRO

GENERATOR & WELDER

RENTALS & HIRE

0411 961 231

WWW.CIVILPRO.COM.AU



PORTABLE POWER

POWERED by
HONDA™

mecc alte spa

Technical

Model	GH 6000E
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max power kW	6.0kW
Continuous Output	7.5kVA
Noise Level (dBA @ 7m)	72
Frame	Extra Large roll frame

Engine

Manufacturer	Honda
Engine Model	GX390
Type	O.H.V.
Starting	Recoil & Electric start
Fuel	Unleaded Petrol
Run Time	2.6 hr @ 100%, 3.8hrs @60%
Tank Capacity	6.1 L
HP 3000 rpm cont	8.0 HP
Cubic Capacity	389 Cm ³
Oil Capacity	1.1 L

Alternator

Alternator Brand	Meccalte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Outlets

Outlet	10amp + 15amp switched with thermal overload
---------------	--

Dimensions & Weight

Length	85 Cm
Width	57 Cm
Height	60 Cm
Weight	58 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Wheel kits	Two wheel or four wheel
Frames	Extra large Roll Frames
Alternators	Oversized, Single or Three Phase
Long Range Tank	15 Litre Capacity

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.