



CIVILPRO

GENERATOR & WELDER

RENTALS & HIRE

0411 961 231

WWW.CIVILPRO.COM.AU



PORTABLE WELDER

POWERED by
HONDA™



Technical

| | |
|-------------------------------|------------------------|
| Model | GHW200/7E |
| Type | Portable |
| Speed | 3000 RPM |
| Phase/Voltage | 1/240 |
| Frequency | 50 Hz |
| Welding Duty Cycle 35% | 200 amp AC |
| Welding Duty Cycle 60% | 180 amp AC |
| Strike Voltage | 75 V |
| Output kVA / kW | 7.0 kVA / 5.6 kW |
| Noise Level (dBA @ 7m) | 72 |
| Frame | Extra Large roll frame |

Engine

| | |
|-------------------------|----------------------------|
| Manufacturer | Honda |
| Engine Model | GX390 |
| Type | O.H.V. |
| Starting | Recoil & Electric start |
| Fuel | Unleaded Petrol |
| Run Time | 2.6 hr @ 100%, 3.8hrs @60% |
| Tank Capacity | 6.1 L |
| HP 3000 rpm cont | 8.0 HP |
| Cubic Capacity | 389 Cm3 |
| Oil Capacity | 1.1 L |

Alternator

| | |
|----------------------------|--------------|
| Alternator Brand | Sincro |
| Type | Brushless |
| Harmonic Distortion | Less than 5% |
| Protection Class | IP 23 |
| Insulation Class | Class H |

Fittings

| | |
|---------------|--|
| Outlet | 10amp + 15amp switched with thermal overload |
| Leads | 5m Leads with Electrode Holder and Earth Clamp |

Dimensions & Weight

| | |
|---------------|-------|
| Length | 85 Cm |
| Width | 57 Cm |
| Height | 60 Cm |
| Weight | 80 Kg |

Options

| | |
|----------------------|--|
| Outlets | Weather protected IP33 & Weatherproof IP66 |
| Protection | RCD/ELCB IP30 or IP66 |
| Wheel kits | Two wheel or four wheel |
| Frames | Extra large Roll Frames |
| Welding Leads | Leads made to measure |
| Fuel Tank | 15 Litre Long Range Tank |

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.