



CIVILPRO

GENERATOR & WELDER

RENTALS & HIRE

0411 961 231

WWW.CIVILPRO.COM.AU



DEPENDABLE POWER

C Series Cummins Diesel

Stamford Alternator



Deep Sea Controls



Technical

Model	OZC175SA
Type	Heavy Duty
Speed	1500 RPM
Phase/Voltage	3, 240 / 415
Frequency	50 Hz
Stdby Power kVA/kW	190kVA / 152kW
Prime Output kVA / kW	175 kVA / 140kW
Noise Level (dBA @ 7m)	71.5dB(A)
Fuel Capacity	24 Hrs 880 Litres

Engine

Manufacturer	Cummins Diesel
Engine Model	6CTA8.3G2
Type & Cylinder	4 Stoke - 6 L
Induction	Turbocharged After Cooled
Fuel Consumption	40 L @ 100%, 30L @ 75%, 20L @ 50% Load
Coolant Capacity	13 L
Governor	Electronic
Cubic Capacity	8.3 L
Oil Capacity	23 L
Warranty	World Wide as per 3381307 Publication

Alternator

Alternator Brand / Model	Stamford / UCI274G
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Canopy

Skid	Bunded fuel tank with fork lift pockets and skid tie down points
Canopy	Centre Lift, lockable doors with control panel viewing window
Paint Finish	Heavy duty powder coat finish white canopy with a black base
Emergency Stop	External Emergency Stop Fitted

Dimensions & Weight

Length	3.42m
Width	1.15m
Height	2.18m
Weight	2769 Kg

Controls

Controller	Deep Sea 5220 with LCD Display
Circuit Breaker	ABB Moulded Case 3 Pole
Battery Isolator	Fitted with canopy adjacent battery

Options

Outlets	Weather protected IP52 or Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.