



CIVILPRO

GENERATOR & WELDER

RENTALS & HIRE

0411 961 231

WWW.CIVILPRO.COM.AU



DEPENDABLE POWER

**B Series Cummins
Diesel**

Stamford Alternator



Deep Sea Controls



Technical

Model	OZC30SA
Type	Heavy Duty
Speed	1500 RPM
Phase/Voltage	3, 240 / 415
Frequency	50 Hz
Stdby Power kVA/kW	33kVA / 26kW
Prime Output kVA / kW	30 kVA / 24kW
Noise Level (dBA @ 7m)	67dB(A)
Fuel Capacity	24 Hrs 220 Litres

Engine

Manufacturer	Cummins Diesel
Engine Model	4B3.9G2
Type & Cylinder	4 Stoke - 4 L
Induction	Naturally Aspirated
Fuel Consumption	6.7L @ 100%, 5.2L @ 75%, 4.0L @ 50% Load
Coolant Capacity	8 L
Governor	Electronic
Cubic Capacity	3.9 L
Oil Capacity	11 L
Warranty	World Wide as per 3381307 Publication

Alternator

Alternator Brand / Model	Stamford / BCI184G - PI144G
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Canopy

Skid	Bunded fuel tank with fork lift pockets and skid tie down points
Canopy	Centre Lift, lockable doors with control panel viewing window
Paint Finish	Heavy duty powder coat finish white canopy with a black base
Emergency Stop	External Emergency Stop Fitted

Dimensions & Weight

Length	2.34m
Width	1.05m
Height	1.55m
Weight	1,288 Kg

Controls

Controller	Deep Sea 5220 with LCD Display
Circuit Breaker	ABB Moulded Case 3 Pole
Battery Isolator	Fitted with canopy adjacent battery

Options

Outlets	Weather protected IP52 or Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
PMG	Available with PI144G

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.